















Benefits



- · Loading capacity up to 625Kg
- · Excellent stability of the cabinet
- · Available in flat pack mode: 70% pre mounted

STRONG MECHANICAL STRUCTURE

- Frame 20/10 thickness offer an excellent stability to the cabinet even in case of maximum loading
- 2 reinforced bar to offer a loading capacity tested up to 625Kg
- Single roof equipped with perforation for natural ventilation and pre cut entry to offer an acces inside the cabinet
- · Reinforced roof to avoid any steel distorsion
- 19" front mounting, 20/10 thickness, in galvanized steel to ensure an electrical continuity to the ground: hole management cable available on mounting cabinet width 800
- Numbering of U in the two ways: make the cabling easier if you start from top or bottom
- · Adjustable mounting depth
- 270° opening doors for a better cabinet accesibility
- · Secure and tempered glass front door equipped with a locking system
- · Doors are equipped with a safe system to realease the doors
- Rear panel
- Quick release side and rear panel with 1/4 turn (without key)
- Empty base for full access inside the cabinet

FLAT PACKING AVAILABLE

- Mode flat pack available with 70% pre assembled cabinet, to make easier access to narrow space and save space storage
- Cabinet assembly 20 minutes
















DIMENSIONS







REF	Н	Hυ	W	Wυ	D	Dυ	WEIGHT
ES2766	1323	1200	609	526	676	610	66.6 Kg
ES4266	1990	1867	609	526	676	610	88.6 Kg
ES4268	1990	1867	609	526	876	810	100 Kg
ES4286	1990	1867	809	726	676	610	105 Kg
ES4288	1990	1867	809	726	876	810	115 Kg

FLAT PACKAGING DIMENSION

P/N	Н	W	D	WEIGHT
ES4266X	2100	600	400	88.6 Kg
ES4268X	2100	600	400	100 Kg
ES4286X	2100	800	400	105 Kg
ES4288X	2100	800	400	115 Kg











RELATED PRODUCT

Shelves		
	49PM1U250G	19" modem shelf 1U depth 250mm
	BPFxU450AD	Fixed 19" adjustable shelf: 1U for 450mm depth and 2u for 550mm depth (with rear mounting associated)
	BPG1Uxxx	19" sliding shelf 1U 350 or 550mm depth (with rear mounting associated)
Accessories		
Electrical	BMASSE19	19" grounding kit for cabinet
Ventilation element	ACBxV	Bloc of 2 or 4 ventilators for roof installation
	ACTHERMOST	Thermostat for ACBxV fan
Mechanical element	ACCASTOR	Castor set for Essential and Technic cabinet
	ACJUNCTION	Junction kit for 19" cabinet
	ACJMARx42	19" rear mounting 42U for Essential cabinet 600 or 800mm width
	ACJMAR27	19" rear mounting 27U for Essential cabinet 600mm width
	ACRINGS6	Set of 6 rings for the cable management (only for mounting of 800mm width)

ORDERING INFORMATION

P/N	DESCRIPTION	PACKAGING	WEIGHT
ES2766	19" Essential cabinet 27U 600x600	UNIT	66.6 Kg
ES4266	19" Essential cabinet 42U 600x600	UNIT	88.6 Kg
ES4268	19" Essential cabinet 42U 600x800	UNIT	100 Kg
ES4286	19" Essential cabinet 42U 800x600	UNIT	105 Kg
ES4288	19" Essential cabinet 42U 800x800	UNIT	115 Kg

P/N	DESCRIPTION	PACKAGING	WEIGHT
ES4266X	19" Flat pack Essential cabinet 42U 600x600	Flat packaging	88.6 Kg
ES4268X	19" Flat pack Essential cabinet 42U 600x800	Flat packaging	100 Kg
ES4286X	19" Flat pack Essential cabinet 42U 800x600	Flat packaging	105 Kg
ES4288X	19" Flat pack Essential cabinet 42U 800x800	Flat packaging	115 Kg



