

GRP26-02

Illuminated Warning Sign - French Version

General

The GRP26-02 optical panel is a low current consumption device, using LED technology. The unit also has an internal buzzer with a sound output of 90 dBA, to attract additional attention. It offers easy installation and maintenance with a housing of auto-extinguishing plastic material, and the possibility to flush mount. The unit is supplied with 3 message inserts : Alarme Incendie, Evacuez la zone immédiatement and Extinction en cours.

Information

The unit is ideally suited for use with a fire extinguishing control panel. The various text inserts supplied with the unit can be used to supply exact information about the extinguishing process. And this way ensure that people take the correct action in the affected area. It is key that people are not in the area being extinguished as there are various health hazards associate with the various extinguishing agents.

Flexible

The unit offers various flexible options to ensure it is suitable for every application. The unit can be surface mounted or flush mounted, with options for cable entry from the back or sides. The 3 different easy changeable text inserts allow for easy customization in the field.

Via dip-switch selection, the flash frequency of the led illumination can be adjusted or it can be select to have the illumination steady on. Multiple units can also be linked together to ensure synchronization between them.



**EVACUEZ LA ZONE
IMMEDIATEMENT**



ALARME INCENDIE



**EXTINCTION
EN COURS**

Details

- Aesthetic design
- Low power consumption
- 90dBA output level
- Easy installation
- High output led illumination
- EN54-3 approved

GRP26-02

Illuminated Warning Sign - French Version

Technical specifications

Electrical

Operating voltage 20 to 30 VDC

VID

Flash frequency 0.6 or 1.1 Hz
36 or 66 flashes /min

Physical

Physical dimensions 305 x 115 x 40 mm

Environmental

Operating temperature -10 to +55°C

Storage temperature -20 to +70°C

Relative humidity 0 to 95% noncondensing

Environment Indoor

IP rating IP41C

Regulatory

Certification EN54-3

Supply voltage

20VDC to 30VDC

Current consumption

70mA @ 24VDC

Sound output @ 1 meter

90 dBA

Flash rate

0.6 Hz or 1.1Hz

Operating temperature

-10° to +55°C

Storage temperature

-20° to +70°C

Relative humidity

0 - 95% (without condensation)

Dimensions (L x H x S)

305 x 115 x 40 mm

Ingress protection

IP41C

Type

A - for indoor use

Housing

ABS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 April 2023 - 15:21