

MINI

The new MINI readers can be used in both autonomous and centralized installations, already using the standard communication protocol, Wiegand26, allowing you to acquire the capabilities and features of the system to which they are connected.

Compatible with AC Plus and IP Axes

FERMAX

Access Control MINI

Proximity readers and keyboards Wiegand26 allow for an anti-tamper security access control installation, which are activated directly from the controller.



Ref. 5276 1 DOOR WG STAND-ALONE CONTROLLER



12V dc supply. Power supply Ref. 4813 recommended.
 Direct output of 12V dc current and not for door opening systems of 12Vdc. (configurable as dry contact by means of internal jumpers on the controller)
 Manage up to 1000 users, any identifier of any type of technology that supports the reader.
 Keyboard infrared included for programming and configurable monostable or bistable relay output 1-99sg.
 Programming of adding and deleting cards. MASTER keycard.
 Types: card, keyboard, card + keyboard, multcard-keyboard.

Ref. 5277 MIFARE MINI WG PROXIMITY READER



Reading distance 2-5cm aprox.
 Supply 12V dc (9-24V DC).
 Consumption at rest 35mA (close proximity with metals or other readers affect consumption).
 Compatibility: Key/Card 125Khz EM, 13,56MHz HID, Mifare (ISO 14443A).
 Oscillation frequency 125KHz y 13,56MHz.
 6 wires.
 Grade of protection IP54.
 Functioning temperature: -20°C a +60°C.
 Dimensions 103 x 48 x 20 mm.
 Protocol Wiegand 26.
 Compatible with AC PLUS & IP_AXES.

Ref. 5278 MINI KEYPAD WITH PROXIMITY WG



Reading distance 2-5cm aprox.
 Supply: 12V dc (9-18VDC).
 Consumption at rest : 35mA (close proximity with metals or other readers affect consumption)
 Compatibility: MIFARE Cards/keys (ISO 14443A).
 Oscillation frequency: 13,56MHz.
 6 wires.
 Grade of protection: IP54.
 functioning temperature: -20°C a +60°C.
 Dimensions: 122x50x21mm.
 Protocol proximity /keypad transmission format: Wiegand 26 / 4bits.
 Compatible with IP_AXES.

IDENTIFIERS



Ref. 4515



Ref. 23361



Ref. 52740




Ref. 52750


- Ref. 4515** PROXIMITY KEY FERMAX EM 125Khz
- Ref. 23361** PROXIMITY CARD FERMAX EM 125Khz
- Ref. 52740** PROXIMITY KEY FERMAX MIFARE 13,56Mhz
- Ref. 52750** PROXIMITY CARD FERMAX MIFARE 13,56Mhz

Note: The MINI keypad (Ref.5278) is only compatible with MIFARE identifiers (ref.52740 y ref.52750).


INSTALLATION BLUEPRINTS



MINI



AC PLUS



IP AXES