

# KL731

## CONVENTIONAL OPTICAL DETECTOR

### General

---

The KL731 is a conventional optical smoke detector.

With outstanding performance, efficiency and durability, the KL700 series conventional fire detectors is the ideal solution for every installation. They are designed specifically for use with Kilsen conventional fire panels, but may also be connected to most 3rd party industry standard conventional fire panels.

### A fire detector for every need

---

With an attractive design and advanced features, these fire detectors have been designed to cope with difficult and even extreme situations. The series comprises a range of detectors including optical and heat detectors, supporting a universal base that suits every application.

A range of bases are available in standard and deep base variants, including relay bases for low voltage (12 VDC) applications and even supports a base variant that compensates for uneven mounting surfaces.

All bases are provided with an integral locking mechanism for extra security, and all detectors support the connection of a remote indicator.

### KL731 Photoelectric Smoke Detector

---

These detectors use the Tyndall effect of smoke in the chamber to detect a fire. It can detect a smouldering fire (without flames). The KL731 detectors are normally used in areas where possible fires generate visible smoke e.g. plastics, polystyrene, PVC, etc.



### Details

---

- An ultra-fine grid prevents the ingress of dust and insects in smoke detectors
- Attractive, low-profile design
- EN54 approved and CPR Certified
- Innovative base option to compensate for uneven surfaces

# KL731

## CONVENTIONAL OPTICAL DETECTOR

### Technical specifications

---

#### Electrical

---

Operating voltage	9 to 28 VDC
-------------------	-------------

---

#### Physical

---

Physical dimensions	45 x 99 mm (h x Ø)
---------------------	--------------------

---

Colour	White (RAL 9010-P)
--------	--------------------

---

#### Environmental

---

Operating temperature	-10 to +70°C
-----------------------	--------------

---

Storage temperature	-10 to +70°C
---------------------	--------------

---

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

---

Environment	Indoor
-------------	--------

---

IP rating	IP42
-----------	------

---

#### Standards & regulation

---

Certification	EN54-7
---------------	--------

---

#### Current consumption

---

Quiescent at 24 VDC	85 µA
---------------------	-------

---

Alarm at 24 VDC	< 100 mA
-----------------	----------

---

#### Remote indicator output

---

	< 100 mA
--	----------

---

#### Number of detectors per zone

---

	20
--	----

---

#### Approvals\*

---

	EN54:7, CPD/R
--	---------------

---

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 10 March 2020 - 10:01