

# KL735A

## KL700A Series Addressable Dual (Optical and Heat) Detector

### General

---

The KL700A series detectors use an enhanced protocol that ensures the overall integrity and error free operation of the system. All detectors are compatible with a standard base and support the connection of a remote indicator.

### KL710A Heat Detector

---

An alarm is raised when the temperature exceeds a fixed temperature or the rate-of-rise of temperature is exceeded. It is used where a fire could cause an abrupt elevation of the temperature, or where smoke of controlled combustion, aerosols, etc. do not allow the use of any other type of detector.

### KL731A/B Optical Smoke Detectors

---

The Tyndall optical effect of smoke in a chamber is used to detect a fire. It is used in areas where possible combustible materials, like plastics, polystyrene, PVC, etc., generate visible smoke.

For installations with false ceilings or black ceilings where detectors should not be visible, this device is also available in black with a black detector base.

The addressable optical detector is available in either white or black colours.

### KL735A Dual Detector

---

Dual technology (one photoelectric and two heat sensors) is used for accurate detection of various types of fires. The heat detection is based on a fixed and rate-of-rise response whilst the photoelectric sensor uses the Tyndall optical effect.

### User Friendly

---

Detectors are identified by soft addressing. The address is stored in flash memory and eliminates the risk of addresses being changed without authorization. Other addressable accessories include conventional zone monitors, various in- and output units, sounder controllers, manual call points and isolators.



### Details

---

- Remote signalling capabilities
- Combination optical and temperature detection with fixed and rate-of-rise heat options
- Easy soft addressing (1-125)
- SMD technology
- Reliable communication protocol
- Full diagnostic self testing
- Full range: Optical, Heat and Dual detectors (optical/heat)
- Full range of supporting I/O units and accessories
- EN54 Approved and CPR certified

# KL735A

## KL700A Series Addressable Dual (Optical and Heat) Detector

### Technical specifications

---

#### General

Status indication	Red (dual LED, alarm)
-------------------	-----------------------

---

#### Electrical

Operating voltage	22 to 38 VDC
Current consumption	350 $\mu$ A (quiescent at 38 VDC) < 5 mA (in alarm)

---

#### Detection

Coverage area	60 to 80 m <sup>2</sup>
---------------	-------------------------

---

#### Output

Remote alarm output	available
---------------------	-----------

---

#### Physical

Physical dimensions	51 x 99 mm (H x Ø)
Net weight	109 g
Colour	White (RAL 9010-P)

---

#### Environmental

Operating temperature	-10 to +70°C
Storage temperature	-10 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP42

---

#### Standards & regulation

Certification	EN54-7
---------------	--------

---

