

# VV602-PLUS

## Seismic detector for ATMs and night safe deposit boxes

### Superior Detection

---

The VV 600 Plus series seismic detectors are designed to detect attempts to break into vaults, safes, night deposit boxes, automatic teller machines (ATM's) and other reinforced physical areas such as data storage's and filing cabinets. These seismic detectors react to the characteristic vibration patterns of all breaking-and-entering tools, such as hammers, drills, diamond saws, hydraulic pressure tools and thermal tools like welding torch and thermal lance. They sense vibrations that occur within a 3 to 14 meter radius of where they are mounted, depending on the material and design of the protected object.

### Excellent false alarm immunity

---

At the same time the seismic detectors allow for normal human activity around the protected area without the risk of creating unwanted alarms. To achieve this high level of accuracy, each detector features "three detectors in one". All three channels (counting, integration, and explosion) analyse the signal frequencies, duration and amplitude, in order to differentiate between random environmental disturbances and real intruder attack. The end result is detectors with excellent detection and false alarm immunity.

### Testing & accessories

---

The VV 600 Plus series provides two different test functions: automatic or manual activated. You can choose between internal test of the detector electronics or, by using the test transmitter VT705P, do a functional test of the detector and its physical contact to the protected object. A complete range of accessories is provided for all kinds of applications to achieve the highest security.



### Details

---

- Detects all known methods of attacks
- Advanced signal processing differentiates between ambient noise and real attacks
- Extremely low current draw
- Two options of testing
- Adjustable sensitivity
- Full-scale tamper protection
- Complete line of accessories
- Easy to install
- Test output screw no.4 for measuring ambient noise level

# VV602-PLUS

## Seismic detector for ATMs and night safe deposit boxes

### Spécifications techniques

---

#### Généralités

Type d'application	Distributeur de billets (DAB), Boîtes de dépôt de sécurité de nuit
Autoprotection	Température 84 ° C, écran de perçage, contact d'ouverture, contact de sécurité
Signal d'alarme	Vis d'indication LED no. 3
Alarme de basse tension	7.5 V

#### Détection

Portée	Rayon de 3 à 14 m
Réglage de la sensibilité	5 étapes d'env. 6 dB chacun

#### Entrées/sorties

Contact d'alarme	Former un relais d'état solide, max 35 ohm de série résistance
Test de sortie	Oui

#### Électrique

Valeur de l'alimentation	9 to 15 VDC
Consommation de courant	8.6 mA (nominal)

#### Caractéristiques physiques

Dimensions physiques	81 x 101 x 28 mm (W x H x D)
Poids net	380 g
Couleur	Gris (RAL 7035)

#### Environnement

Température de fonctionnement	-20 to +55°C
Humidité relative	0 to 90% noncondensing; 90% at 30°C
Indice de protection	IP30

